



ATC ATIK IMHA SISTEMLERİ LTD STİ

P : +90 322 459 0660 F : +90 322 459 0661 C : 0 532 580 6723

E-mail : atc@atcgow.com Web : www.atcgow.com

Resatbey Mah. Fuzuli Cad. Nehir Apt., Kat:2, Daire:5, Seyhan/Adana/TURKEY

www.atcint.com.tr

www.atcincinerator.com

www.atcsondaj.com

LOW TEMPERATURE EUTECTIC PLATES WITH SOLUTION AT -33°C



Eutectic plates refrigeration uses frozen eutectic plates inside the body compartment to absorb heat to maintain the desired temperature levels. Those passive plates are “refrozen” each day during 10 /12 hours connecting them to the refrigerant compressor by means of an electrical plug. The freezing temperature of the eutectic solution is -33°C. The eutectic plates are filled with a solution that freezes at a specific temperature (eutectic point). By connecting a condensing unit to the pipe that is inside the eutectic plate it is possible to freeze the eutectic solution. In this way we produce an independent storage of cold at a well determined temperature, which is proportional to the quantity of eutectic solution and to its melting latent heat. The eutectic plates are used to maintain the temperature of the product which is already refrigerated or frozen. The exchange coefficient of the plates is of about 13.95 W/m²°C.